



Email all enquiries to: **sales@tcrderby.com**
 Tel: 01332 208206
 Fax back to: 01332 208204
 Text / WhatsApp: 07940438419

WARMERROOF ENQUIRY

Date:

Company Name:

Job Reference:

Tel No:

Please illustrate an accurate roof survey below with all host wall positions clearly marked. Please indicate all facet angles. All dimensions are internal frame and are in millimetres unless stated otherwise.

o/all Internal width (mm)

o/all Internal projection (mm)

ROOF PLAN

For any unsupported sections (e.g Bi-fold doors) please send your full frame layout with your roof enquiry

FRAMEWORK



Installer to ensure there is adequate support for this roof. TCR (Derby) Ltd will not be held responsible for the failure of members, or existing structures supporting this roof.

70mm 60mm Other (Please specify)

TILE COLOUR - METROTILE / TAPCO OPTIONS

Metrotile

Shingle :Lowest pitch = 15°

- Charcoal
- Antique Red
- Burnt Umber
- Moss Green
- Ebony
- Coal Black
- Bister Brown
- Iron Bark
- Scarlet

Tapco Slate

Lowest pitch = 15°

- Brick Red
- Pewter Grey
- Stone Black
- Chestnut Brown
- Plum
- Red Rock

TILE COLOUR - BRITMET SHINGLE/SLATE OPTIONS

Britmet Shingle

Shingle :Lowest pitch = 15°

- Titanium Grey
- Rustic Red
- Smoked Oak
- Tartan Green
- Moss Gree
- Raven
- Bramble Brown
- Rustic Brown
- Rustic Terracota

Britmet PVC Slate

Lowest pitch = 12°

- Sunset
- Slate Grey
- Charcoal
- Oak
- Amethyst
- Ash

FASCIA

- White
- Cream
- Golden Oak
- Irish Oak
- Rosewood
- 7016 Grey
- Black Ash
- Chartwell Green

GUTTER

- (Ogee)
- White
 - Brown
 - 7016 Grey
 - Black
- Downpipe
- Square
 - Round

VENTS

Please indicate position on survey above. Lowest pitch = 15°

- Small (550 x 780)
- Large (780 x 980)
- Manual (pole supplied)
- Electric (make selection)
- Remote & Rain Sensor
- Solar

- Extras
- Integral Blinds
 - Pull down Blinds

FIXED GLASS PLATES

Please indicate position on survey above. Lowest pitch = 15°

* All glass plates are 600mm wide and run full length of roof

- Yes No
- Clear Glass
- Blue Glass

Required glass thickness - 28mm

EXTRAS

Please ensure these are priced separately quotation.

- External soffit (Depth 150mm)
- Internal pelmet (Depth 300mm)

SUPPORT

Steel reinforcement added to ring beam to support bi-fold door opening. Seek advice from a member of staff for max spans

- Yes (Please indicate position on survey)
- No

ROOF HEIGHT

Roof pitch if known (degrees)

Frame height from DPC (including cill)

Internal height

External height

In normal circumstances Local Authority Building Control is required for new or replacement conservatory roofs and it is the installers responsibility to check whether Building Control is required. Although the Warmer Roof has JHAI Building Control accreditation, this does not mean that Building Control is not required but having this accreditation, through JHAI, simplifies the Building Control application. It is likely that site inspection (s) will be carried out during the installation procedure of a replacement or new conservatory roof. TCR (Derby) Ltd holds no responsibility if this advice is not followed. The Warmer Roof is only tested and certified by JHAI Ltd Building Control. TCR (Derby) Ltd will not take responsibility for any other Building Control other than JHAI Ltd. Please contact a member of staff if any further guidance is required. Our conditions of sale shall apply to the sale of the goods to the exclusion of all other terms, unless agreed in writing by TCR (Derby) Ltd.

